

# HIGH PRESSURE LAMINATE POLYREY HPL®

Interior Fitting



- NEW CONSTRUCTION**  
 **REFURBISHMENT**

**LEED v4 - Building Design and Construction (BD+C)**  
 Office (O) - Retail (R) - Hospitality (Ho) - Healthcare (He)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Credit category		Credit	Requirement - Polyrey product contribution	Points
 <b>MR</b> MATERIALS AND RESOURCES	<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>		Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
			Option 2 - Leadership extraction practice - Product made from PEFC™ or FSC® certified wood	1 pt
	<b>Furniture and medical furnishings</b>		Option 1 - Minimal chemical content and/or Option 2 - Testing and Modeling of Chemical Content - Chemically inert material	He : Up to 2 pts
			Option 3 - Multi-Attribute Assessment of Products - Product made from PEFC™ or FSC® certified wood and with a conform life cycle analysis	He : Up to 2 pts
 <b>EQ</b> INDOOR ENVIRONMENTAL QUALITY	<b>Low-emitting materials</b>		Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified.	Up to 3 pts
	<b>Interior lighting</b>		Option 2 - Lighting quality - Product easing natural lightening	O : 1 pt Ho : 1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation	
<b>Building Product Disclosure and Optimization</b> <b>Environmental Product Declarations</b> Option 1 - Environmental Product Declaration (EPD)	<b>USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.</b>  <b>Product with conform life cycle analysis</b> Indirect influence: Polyrey has carried out Life Cycle Analysis (LCA) for POLYREY HPL® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations.  1 pt <ul style="list-style-type: none"> <li>• ATT - FDES - Polyrey HPL contrecollé sur panneaux bois - FR</li> <li>• ATT - EPD - Polyrey HPL Bonded board - EN</li> </ul>	
<b>Building Product Disclosure and Optimization</b> <b>Sourcing of Raw Materials</b> Option 2 - Leadership extraction practice	<b>USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).</b>  <b>Product made from PEFC™ or FSC® certified wood</b> Direct influence: POLYREY HPL® meets 2 responsible supply criteria: - All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last) - 20 % recycled content  Moreover, Polyrey has two production plants in France : Baneuil (24) and Ussel (19).  1 pt <ul style="list-style-type: none"> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> <li>• ATT - Self declared environmental claim - Polyrey HPL - FR - EN</li> </ul>	
<b>Furniture and medical furnishings</b> Option 1 - Minimal chemical content and / or Option 2 - Testing and Modeling of Chemical Content	<b>ALL COMPONENTS COMPRISING AT LEAST 5% OF THE WEIGHT OF A FURNISHING MUST CONTAIN LESS THAN 100 PPM OF AT LEAST 4 OF THE 5 CHEMICAL GROUPS.</b>  <b>Chemically inert material</b> Direct influence: POLYREY HPL®: - 0% urea formaldehyde; - 0% heavy metals including mercury, cadmium, lead and antimony; - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS); - 0% pentachlorophenol - 0% protective products (e.g. lacquer, varnish etc.)  He : Up to 2 pts As for all its products, POLYREY HPL® contains no chemical substances included in the candidate list of Substances of Very High Concern - SVHC - in concentrations higher than 0.1% of the mass. In addition, POLYREY HPL® is Greenguard Gold certified. This label provides proof of compliance with the standard no. ANSI/BIFMA e3-2011.  <ul style="list-style-type: none"> <li>• ATT - Certificate of compliance Polyrey HPL and Reysipur composition - FR - EN</li> <li>• ATT - Certificate of compliance REACH - FR - EN</li> <li>• ATT - Certificate of compliance RoHS - FR - EN</li> <li>• ATT - Greenguard Gold certificate - Polyrey HPL - EN</li> </ul>	
<b>Furniture and medical furnishings</b> Option 3 - Multi-Attribute Assessment of Products	<b>USE PRODUCTS THAT MEET ONE OF THE FOLLOWING CRITERIA:</b> <b>- COMPLIANT ENVIRONMENTAL DECLARATION</b> <b>- RESPONSIBLE SUPPLY</b>  <b>Product made from PEFC™ or FSC® certified wood and with a conform life cycle analysis</b> Direct influence: Polyrey has carried out Life Cycle Analysis (LCA) for POLYREY HPL® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations. All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request*, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests. and contains 20% recycled material. *Depending on the certification of our suppliers, while stocks last  He : Up to 2 pts <ul style="list-style-type: none"> <li>• ATT - FDES - Polyrey HPL contrecollé sur panneaux bois - FR</li> <li>• ATT - EPD - Polyrey HPL Bonded board - EN</li> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - Self declared environmental claim - Polyrey HPL - FR - EN</li> </ul>	



# EQ - INDOOR ENVIRONMENTAL QUALITY

**Criterion** Requirement - Polyrey product contribution - Documentation

**RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.**

**Low-emitting materials**

Option 1 - Product category calculations  
or Option 2 - Budget calculation method

Up to 3 pts

**Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified.**

Direct influence: POLYREY HPL® is Greenguard Gold certified, certification recognised by the document "LEED V4 EQ Credit low emitting materials third party certifications and labels". Moreover, this label is internationally recognised as proof of compliance with the strictest requirements in terms of indoor air quality, in accordance with the emissions criterion used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies. The Greenguard Gold certification uses the strictest threshold limits to account for sensitive people (children and the elderly). Over 360 VOCs evaluated with a limit value for Total Volatile Organic Compounds (TVOC).

	CLASSIFICATION	COVT	FORMALDEHYDE
		MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS	
POLYREY HPL®	<b>GREENGUARD GOLD</b>	≤ 0,22 0,007 mg/m³	≤ 0,0073 0,007 ppm

**NOTA: French VOC labelling**

In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. POLYREY HPL® has received the following classification:

	CLASSIFICATION	COVT	FORMALDEHYDE
		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS	
POLYREY HPL® WALL SCENARIO	<b>A</b>	< 1000 7,2 µg/m³	< 60 15 µg/m³
POLYREY HPL® TOUCH FINISH ALL SCENARIOS	<b>A+</b>	< 1000 19 µg/m³	< 10 7,4 µg/m³
POLYREY HPL® DOOR SCENARIO	<b>A+</b>	< 1000 0,4 µg/m³	< 10 0,8 µg/m³

- ATT - Greenguard Gold certificate - Polyrey HPL - EN
- PV - Report of classification COV - Wall - Polyrey HPL
- PV - Report of classification COV - Door - Polyrey HPL - FR - EN
- PV - Report of classification COV - Wall - Polyrey HPL Touch - FR - EN

**CHOSE 4 OF THE 8 SOLUTIONS AVAILABLE WHICH GUARANTEE QUALITY LIGHTING.**

**Interior lighting**

Option 2 - Lighting quality

O : 1 pt  
Ho : 1 pt

**Product easing natural lighting**

Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings.

With its large range of over 300 decors (plain, wood, materials), Polyrey HPL® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.

- DOC - Light Reflectance Values

MY EXPERT



Environmental advice

Do not hesitate to contact us. Our team is at your disposal to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

DOWNLOAD ALL DOCUMENTARY PROOFS HERE :



# HIGH PRESSURE LAMINATE POLYREY HPL®

Interior Fitting



- NEW CONSTRUCTION
- REFURBISHMENT

LEED v4 - Interior Design and Construction (ID+C)  
Office (O) - Retail (R) - Hospitality (Ho)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Credit category		Credit	Requirement - Polyrey product contribution	Points
 MR MATERIALS AND RESOURCES		<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>	Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
		<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b>	Option 2 - Leadership extraction practice - Product made from PEFC™ or FSC® certified wood	1 pt
		<b>Building Product Disclosure and Optimization - Material Ingredients</b>	Option 2 - Material Ingredient Optimization - Chemically inert material	1 pt
 EQ INDOOR ENVIRONMENTAL QUALITY		<b>Low-emitting materials</b>	Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified.	Up to 3 pts
		<b>Interior lighting</b>	Option 2 - Lighting quality - Product easing natural lightening	1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation	
<b>Building Product Disclosure and Optimization</b> - <b>Environmental Product Declarations</b> Option 1 - Environmental Product Declaration (EPD)	USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.  1 pt	<b>Product with conform life cycle analysis</b> Indirect influence: Polyrey has carried out Life Cycle Analysis (LCA) for POLYREY HPL® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations.  <ul style="list-style-type: none"> <li>• ATT - FDES - Polyrey HPL contrecollé sur panneaux bois - FR</li> <li>• ATT - EPD - Polyrey HPL Bonded board - EN</li> </ul>
<b>Building Product Disclosure and Optimization</b> - <b>Sourcing of Raw Materials</b> Option 2 - Leadership extraction practice	USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).  1 pt	<b>Product made from PEFC™ or FSC® certified wood</b> Direct influence: POLYREY HPL® meets 2 responsible supply criteria: - All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last) - 20% recycled content  Moreover, Polyrey has two production plants in France : Baneuil (24) and Ussel (19).  <ul style="list-style-type: none"> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> <li>• ATT - Self declared environmental claim - Polyrey HPL - FR - EN</li> </ul>
<b>Building Product Disclosure and Optimization</b> - <b>Material Ingredients</b> Option 2 - Material Ingredient Optimization	USE A CERTAIN NUMBER OF PRODUCTS WITH PRE-EVALUATED COMPONENTS.  1 pt	<b>Chemically inert material</b> Direct influence: POLYREY HPL®: - 0% urea formaldehyde; - 0% heavy metals including mercury, cadmium, lead and antimony; - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS); - 0% pentachlorophenol - 0% protective products (e.g. lacquer, varnish etc.)  As for all its products, POLYREY HPL® contains no chemical substances included in the candidate list of Substances of Very High Concern – SVHC - in concentrations higher than 0.1% of the mass. In addition, POLYREY HPL® is Greenguard Gold certified. This label provides proof of compliance with the standard no. ANSI/BIFMA e3-2011.  <ul style="list-style-type: none"> <li>• ATT - Certificate of compliance Polyrey HPL and Reysipur composition - FR - EN</li> <li>• ATT - Certificate of compliance REACH - FR - EN</li> <li>• ATT - Certificate of compliance RoHS - FR - EN</li> <li>• ATT - Greenguard Gold certificate - Polyrey HPL - EN</li> </ul>



# EQ - INDOOR ENVIRONMENTAL QUALITY

**Criterion** Requirement - Polyrey product contribution - Documentation

**RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.**

**Low-emitting materials**  
Option 1 - Product category calculations  
or Option 2 - Budget calculation method

**Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified.**  
Direct influence: POLYREY HPL® is Greenguard Gold certified, certification recognised by the document "LEED V4 EQ Credit low emitting materials third party certifications and labels". Moreover, this label is internationally recognised as proof of compliance with the strictest requirements in terms of indoor air quality, in accordance with the emissions criterion used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies. The Greenguard Gold certification uses the strictest threshold limits to account for sensitive people (children and the elderly). Over 360 VOCs evaluated with a limit value for Total Volatile Organic Compounds (TVOC).

POLYREY HPL®	CLASSIFICATION	COVT	FORMALDEHYDE
		MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS	
	<b>GREENGUARD GOLD</b>	≤ <b>0,22</b> 0,007 mg/m <sup>3</sup>	≤ <b>0,0073</b> 0,007 ppm

**NOTA : French VOC labelling**  
In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. POLYREY HPL® has received the following classification:

POLYREY HPL®	CLASSIFICATION	COVT	FORMALDEHYDE
		MAXIMUM CONCENTRATIONS (µg/m <sup>3</sup> ) - MEASURED AFTER 28 DAYS	
<b>WALL SCENARIO</b>	<b>A</b>	< <b>1000</b> 7,2 µg/m <sup>3</sup>	< <b>60</b> 15 µg/m <sup>3</sup>
<b>TOUCH FINISH ALL SCENARIOS</b>	<b>A +</b>	< <b>1000</b> 19 µg/m <sup>3</sup>	< <b>10</b> 7,4 µg/m <sup>3</sup>
<b>DOOR SCENARIO</b>	<b>A +</b>	< <b>1000</b> 0,4 µg/m <sup>3</sup>	< <b>10</b> 0,8 µg/m <sup>3</sup>

- AIT - Greenguard Gold certificate - Polyrey HPL - EN
- PV - Report of classification COV - Wall - Polyrey HPL
- PV - Report of classification COV - Door - Polyrey HPL - FR - EN
- PV - Report of classification COV - Wall - Polyrey HPL Touch - FR - EN

**CHOSE 4 OF THE 8 SOLUTIONS AVAILABLE WHICH GUARANTEE QUALITY LIGHTING.**

**Interior lighting**  
Option 2 - Lighting quality

**Product easing natural lighting**  
Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 300 decors (plain, wood, materials), Polyrey HPL® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.

- DOC - Light Reflectance Values

Environmental advice

Do not hesitate to contact us.  
Our team is at your disposal  
to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

**DOWNLOAD ALL DOCUMENTARY PROOFS HERE :**



## COMPACT HPL REYSIPUR®

Interior Fitting

**NEW CONSTRUCTION**

**REFURBISHMENT**

**LEED v4 - Building Design and Construction (BD+C)**  
Office (O) - Retail (R) - Hospitality (Ho) - Healthcare (He)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Section	Issue	Criterion - Polyrey product contribution	Points
 <p><b>MR</b> MATERIALS AND RESOURCES</p>	<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>	Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
	<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b>	Option 2 - Leadership extraction practice - Product made from PEFC™ or FSC® certified wood	1 pt
	<b>Furniture and medical furnishings</b>	Option 1 - Minimal chemical content and/or Option 2 - Testing and Modeling of Chemical Content - Chemically inert material	He : Up to 2 pts
		Option 3 - Multi-Attribute Assessment of Products - Product made from PEFC™ or FSC® certified wood and with a conform life cycle analysis	He : Up to 2 pts
 <p><b>EQ</b> INDOOR ENVIRONMENTAL QUALITY</p>	<b>Low-emitting materials</b>	Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified.	Up to 3 pts
	<b>Interior lighting</b>	Option 2 - Lighting quality - Product easing natural lightening	O : 1 pt Ho : 1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation
<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b> Option 1 - Environmental Product Declaration (EPD)	<b>USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.</b>
	<p><b>1 pt</b></p> <p><b>Product with conform life cycle analysis</b>                      Direct influence: Polyrey has carried out Life Cycle Analysis (LCA) for REYSIPUR® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations.</p> <ul style="list-style-type: none"> <li>• <a href="#">ATT - POLYREY - FDES - Reysipur - FR</a></li> <li>• <a href="#">ATT - POLYREY - EPD - Reysipur - EN</a></li> </ul>
<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b> Option 2 - Leadership extraction practice	<b>USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).</b>
	<p><b>1 pt</b></p> <p><b>Product made from PEFC™ or FSC® certified wood</b>                      Direct influence: REYSIPUR® fulfils the criteria for responsible sourcing :                      All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last)                      Moreover, Polyrey has two production plants in France : Baneuil (24) and Ussel (19).</p> <ul style="list-style-type: none"> <li>• <a href="#">ATT - PEFC Certificate - EN</a></li> <li>• <a href="#">ATT - FSC Certificate - EN</a></li> <li>• <a href="#">ATT - European Timber regulations RBUE - FR - EN</a></li> </ul>
<b>Furniture and medical furnishings</b> Option 1 - Minimal chemical content and / or Option 2 - Testing and Modeling of Chemical Content	<b>ALL COMPONENTS COMPRISING AT LEAST 5% OF THE WEIGHT OF A FURNISHING MUST CONTAIN LESS THAN 100 PPM OF AT LEAST 4 OF THE 5 CHEMICAL GROUPS.</b>
	<p><b>He : Up to 2 pts</b></p> <p><b>Chemically inert material</b>                      Direct influence: REYSIPUR®:                      - 0% urea formaldehyde;                      - 0% heavy metals including mercury, cadmium, lead and antimony;                      - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS);                      - 0% pentachlorophenol                      - 0% protective products (e.g. lacquer, varnish etc.)                      As for all its products, REYSIPUR® contains no chemical substances included in the candidate list of Substances of Very High Concern – SVHC - in concentrations higher than 0.1% of the mass.                      In addition, REYSIPUR® is Greenguard Gold certified. This label provides proof of compliance with the standard no. ANSI/BIFMA e3-2011.</p> <ul style="list-style-type: none"> <li>• <a href="#">ATT - Certificate of compliance Polyrey HPL and Reysipur composition - FR - EN</a></li> <li>• <a href="#">ATT - Certificate of compliance REACH - FR - EN</a></li> <li>• <a href="#">ATT - Certificate of compliance RoHS - FR - EN</a></li> <li>• <a href="#">ATT - Greenguard Gold certificate - Reysipur - EN</a></li> </ul>
<b>Furniture and medical furnishings</b> Option 3 - Multi-Attribute Assessment of Products	<b>USE PRODUCTS THAT MEET ONE OF THE FOLLOWING CRITERIA:                      - COMPLIANT ENVIRONMENTAL DECLARATION                      - RESPONSIBLE SUPPLY</b>
	<p><b>He : Up to 2 pts</b></p> <p><b>Product made from PEFC™ or FSC® certified wood and with a conform life cycle analysis</b>                      Direct influence: Polyrey has carried out Life Cycle Analysis (LCA) for REYSIPUR® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations.                      All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last)</p> <ul style="list-style-type: none"> <li>• <a href="#">ATT - POLYREY - FDES - Reysipur - FR</a></li> <li>• <a href="#">ATT - POLYREY - EPD - Reysipur - EN</a></li> <li>• <a href="#">ATT - PEFC Certificate - EN</a></li> <li>• <a href="#">ATT - FSC Certificate - EN</a></li> </ul>



# EQ - INDOOR ENVIRONMENTAL QUALITY

Criterion	Requirement - Polyrey product contribution - Documentation																							
<b>Low-emitting materials</b> Option 1 - Product category calculations or Option 2 - Budget calculation method	Up to 3 pts	<p><b>RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.</b></p> <p><b>Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified</b>                      Direct influence: REYSIPUR® is Greenguard Gold certified, certification recognised by the document "LEED V4 EQ Credit low emitting materials third party certifications and labels". Moreover, this label is internationally recognised as proof of compliance with the strictest requirements in terms of indoor air quality, in accordance with the emissions criterion used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies. The Greenguard Gold certification uses the strictest threshold limits to account for sensitive people (children and the elderly). Over 360 VOCs evaluated with a limit value for Total Volatile Organic Compounds (TVOC).</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="width: 20%;">CLASSIFICATION</th> <th style="width: 10%;">COVT</th> <th style="width: 10%;">FORMALDEHYDE</th> </tr> <tr> <th colspan="2" style="text-align: center;">MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">REYSIPUR®</td> <td style="text-align: center;"><b>GREENGUARD GOLD</b></td> <td style="text-align: center;">≤ 0,22 0,007 µg/m³</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">≤ 0,0073 0,001 ppm</td> </tr> </tbody> </table> <p><b>NOTA: French VOC labelling</b>                      In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. REYSIPUR® has received the following classification:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="width: 20%;">CLASSIFICATION</th> <th style="width: 10%;">COVT</th> <th style="width: 10%;">FORMALDEHYDE</th> </tr> <tr> <th colspan="2" style="text-align: center;">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">REYSIPUR® WALL SCENARIO</td> <td style="text-align: center;"><b>A</b></td> <td style="text-align: center;">&lt; 1000 2,9 µg/m³</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">&lt; 60 42 µg/m³</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>• <a href="#">AIT - Greenguard Gold certificate - Reysipur - EN</a></li> <li>• <a href="#">PV - Report of classification COV - Wall - Reysipur</a></li> </ul>	CLASSIFICATION	COVT	FORMALDEHYDE	MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS		REYSIPUR®	<b>GREENGUARD GOLD</b>	≤ 0,22 0,007 µg/m³			≤ 0,0073 0,001 ppm	CLASSIFICATION	COVT	FORMALDEHYDE	MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS		REYSIPUR® WALL SCENARIO	<b>A</b>	< 1000 2,9 µg/m³			< 60 42 µg/m³
	CLASSIFICATION	COVT		FORMALDEHYDE																				
MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS																								
REYSIPUR®	<b>GREENGUARD GOLD</b>	≤ 0,22 0,007 µg/m³																						
		≤ 0,0073 0,001 ppm																						
CLASSIFICATION	COVT	FORMALDEHYDE																						
	MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS																							
REYSIPUR® WALL SCENARIO	<b>A</b>	< 1000 2,9 µg/m³																						
		< 60 42 µg/m³																						
<b>Interior lighting</b> Option 2 - Lighting quality	0 : 1 pt Ho : 1 pt	<p><b>Product easing natural lighting</b>                      Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 300 decors (plain, wood, materials), REYSIPUR® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.</p> <ul style="list-style-type: none"> <li>• <a href="#">DOC - Light Reflectance Values</a></li> </ul>																						

MY EXPERT



Environmental advice

Do not hesitate to contact us. Our team is at your disposal to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

DOWNLOAD ALL DOCUMENTARY PROOFS HERE :





## COMPACT HPL REYSIPUR®

Interior Fitting

NEW CONSTRUCTION

REFURBISHMENT

LEED v4 - Interior Design and Construction (ID+C)  
Office (O) - Retail (R) - Hospitality (Ho)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Credit category		Credit	Requirement - Polyrey product contribution	Points
 MR MATERIALS AND RESOURCES		<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>	Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
		<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b>	Option 2 - Leadership extraction practice - Product made from PEFC™ or FSC® certified wood	1 pt
		<b>Building Product Disclosure and Optimization - Material Ingredients</b>	Option 2 - Material Ingredient Optimization - Chemically inert material	1 pt
 EQ INDOOR ENVIRONMENTAL QUALITY		<b>Low-emitting materials</b>	Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified	Up to 3 pts
		<b>Interior lighting</b>	Option 2 - Lighting quality - Product easing natural lightening	1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation
<b>Building Product Disclosure and Optimization</b> <i>Environmental Product Declarations</i> Option 1 - Environmental Product Declaration (EPD)	<p><b>USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.</b></p>
	<p>1 pt</p> <p><b>Product with conform life cycle analysis</b>                      Direct influence: Polyrey has carried out Life Cycle Analysis (LCA) for REYSIPUR® in compliance with the NF EN 15804:2012+A1:2014 standard on individual environmental declarations.</p> <ul style="list-style-type: none"> <li>• ATT - POLYREY - FDES - Reysipur - FR</li> <li>• ATT - POLYREY - EPD - Reysipur - EN</li> </ul>
<b>Building Product Disclosure and Optimization</b> <i>Sourcing of Raw Materials</i> Option 2 - Leadership extraction practice	<p><b>USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).</b></p>
	<p>1 pt</p> <p><b>Product made from PEFC™ or FSC® certified wood</b>                      Direct influence: REYSIPUR® fulfils the criteria for responsible sourcing :                      All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last)</p> <p>Moreover, Polyrey has two production plants in France: Baneuil (24) and Ussel (19).</p> <ul style="list-style-type: none"> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> </ul>
<b>Building Product Disclosure and Optimization</b> <i>Material Ingredients</i> Option 2 - Material Ingredient Optimization	<p><b>USE A CERTAIN NUMBER OF PRODUCTS WITH PRE-EVALUATED COMPONENTS.</b></p>
	<p>1 pt</p> <p><b>Chemically inert material</b>                      Direct influence: REYSIPUR®:                      - 0% urea formaldehyde;                      - 0% heavy metals including mercury, cadmium, lead and antimony;                      - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS);                      - 0% pentachlorophenol                      - 0% protective products (e.g. lacquer, varnish etc.)</p> <p>As for all its products, REYSIPUR® contains no chemical substances included in the candidate list of Substances of Very High Concern – SVHC - in concentrations higher than 0.1% of the mass.                      In addition, REYSIPUR® is Greenguard Gold certified. This label provides proof of compliance with the standard no. ANSI/BIFMA e3-2011.</p> <ul style="list-style-type: none"> <li>• ATT - Certificate of compliance Polyrey HPL and Reysipur composition - FR - EN</li> <li>• ATT - Certificate of compliance REACH - FR - EN</li> <li>• ATT - Certificate of compliance RoHS - FR - EN</li> <li>• ATT - Greenguard Gold certificate - Reysipur - EN</li> </ul>



# EQ - INDOOR ENVIRONMENTAL QUALITY

Criterion	Requirement - Polyrey product contribution - Documentation																					
<b>Low-emitting materials</b> Option 1 - Product category calculations or Option 2 - Budget calculation method	<p><b>RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.</b></p> <p><b>Product respecting TVOC and formaldehyde emissions thresholds, and Greenguard Gold certified</b>                      Direct influence: REYSIPUR® is Greenguard Gold certified, certification recognised by the document "LEED V4 EQ Credit low emitting materials third party certifications and labels". Moreover, this label is internationally recognised as proof of compliance with the strictest requirements in terms of indoor air quality, in accordance with the emissions criterion used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies. The Greenguard Gold certification uses the strictest threshold limits to account for sensitive people (children and the elderly). Over 360 VOCs evaluated with a limit value for Total Volatile Organic Compounds (TVOC).</p> <table border="1"> <thead> <tr> <th rowspan="2">REYSIPUR®</th> <th rowspan="2">CLASSIFICATION</th> <th>COVT</th> <th>FORMALDEHYDE</th> </tr> <tr> <th colspan="2">MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS</th> </tr> </thead> <tbody> <tr> <td></td> <td><b>GREENGUARD GOLD</b></td> <td>≤ 0,22 0,007 µg/m³</td> <td>≤ 0,0073 0,001 ppm</td> </tr> </tbody> </table> <p><b>NOTA: French VOC labelling</b>                      In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. REYSIPUR® has received the following classification:</p> <table border="1"> <thead> <tr> <th rowspan="2">REYSIPUR® WALL SCENARIO</th> <th rowspan="2">CLASSIFICATION</th> <th>COVT</th> <th>FORMALDEHYDE</th> </tr> <tr> <th colspan="2">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> </thead> <tbody> <tr> <td></td> <td><b>A</b></td> <td>&lt; 1000 2,9 µg/m³</td> <td>&lt; 60 42 µg/m³</td> </tr> </tbody> </table> <p> <ul style="list-style-type: none"> <li>• <a href="#">AIT - Greenguard Gold certificate - Reysipur - EN</a></li> <li>• <a href="#">PV - Report of classification COV - Wall - Reysipur</a></li> </ul> </p>	REYSIPUR®	CLASSIFICATION	COVT	FORMALDEHYDE	MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS			<b>GREENGUARD GOLD</b>	≤ 0,22 0,007 µg/m³	≤ 0,0073 0,001 ppm	REYSIPUR® WALL SCENARIO	CLASSIFICATION	COVT	FORMALDEHYDE	MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS			<b>A</b>	< 1000 2,9 µg/m³	< 60 42 µg/m³	Up to 3 pts
	REYSIPUR®			CLASSIFICATION	COVT	FORMALDEHYDE																
MAXIMUM CONCENTRATIONS - MEASURED AFTER 7 DAYS																						
	<b>GREENGUARD GOLD</b>	≤ 0,22 0,007 µg/m³	≤ 0,0073 0,001 ppm																			
REYSIPUR® WALL SCENARIO	CLASSIFICATION	COVT	FORMALDEHYDE																			
		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS																				
	<b>A</b>	< 1000 2,9 µg/m³	< 60 42 µg/m³																			
<b>Interior lighting</b> Option 2 - Lighting quality	<p><b>CHOOSE 4 OF THE 8 SOLUTIONS AVAILABLE WHICH GUARANTEE QUALITY LIGHTING.</b></p> <p><b>Product easing natural lighting</b>                      Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 300 decors (plain, wood, materials), REYSIPUR® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.</p> <p> <ul style="list-style-type: none"> <li>• <a href="#">DOC - Light Reflectance Values</a></li> </ul> </p>	1 pt																				

MY EXPERT



Environmental advice

Do not hesitate to contact us. Our team is at your disposal to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

DOWNLOAD ALL DOCUMENTARY PROOFS HERE :



## MELAMINE FACED BOARD PANOPREY®

Interior Fitting



**NEW CONSTRUCTION**  
 **REFURBISHMENT**

**LEED v4 - Building Design and Construction (BD+C)**  
 Office (O) - Retail (R) - Hospitality (Ho) - Healthcare (He)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Credit category		Credit	Requirement - Polyrey product contribution	Points
 <b>MR</b> MATERIALS AND RESOURCES	<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>		Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
			Option 2 - Leadership extraction practice - Product made from PEFC™ ou FSC® certified wood	1 pt
	<b>Furniture and medical furnishings</b>		Option 1 - Minimal chemical content and/or Option 2 - Testing and Modeling of Chemical Content - Chemically inert material	He : Up to 2 pts
			Option 3 - Multi-Attribute Assessment of Products - Product made from PEFC™ ou FSC® certified wood and with a conform life cycle analysis	He : Up to 2 pts
 <b>EQ</b> INDOOR ENVIRONMENTAL QUALITY	<b>Low-emitting materials</b>		Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds	Up to 3 pts
	<b>Interior lighting</b>		Option 2 - Lighting quality - Product easing natural lightening	O : 1 pt Ho : 1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation	
<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b> Option 1 - Environmental Product Declaration (EPD)	<b>USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.</b>	
	1 pt	<p><b>Product with conform life cycle analysis</b>                      Indirect influence: Polyrey has carried out Life Cycle Analysis (LCA) for PANOPREY® in compliance with the NF EN 15804:2012+A1:2014 standard on collective environmental declarations.</p> <ul style="list-style-type: none"> <li>• ATT - FDES - Panoprey - Qualite Standard - FR</li> <li>• ATT - FDES - Panoprey - Qualite Hydrofuge - FR</li> <li>• ATT - EPD - Panoprey - Standard Qualite - EN</li> <li>• ATT - FDES - Panoprey - Moisture resistant Quality EN</li> </ul>
<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b> Option 2 - Leadership extraction practice	<b>USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).</b>	
	1 pt	<p><b>Product made from PEFC™ or FSC® certified wood</b>                      PANOPREY® is:                      - 85% composed of an anhydrous wood core from the following sources: 20% roundwood (twigs, branches, downgraded logs), 37% related products (chips, particles) from other woodworking industries (sawmills, joineries, furniture makers, etc.), 43% secondary raw materials for recycling (chips from wood waste shredding).                      - All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last)                      It is therefore included in the calculation of the volume of wood used in the structure, with reference to the order of 13 September 2010 establishing the method for calculating the volume of wood used in certain constructions.</p> <p>Moreover, Polyrey has one production plant in France : Ussel (19).</p> <ul style="list-style-type: none"> <li>• ATT - PEFC - Certificat - EN Panoprey - Qualite Standard - FR</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> </ul>
<b>Furniture and medical furnishings</b> Option 1 - Minimal chemical content and / or Option 2 - Testing and Modeling of Chemical Content	<b>ALL COMPONENTS COMPRISING AT LEAST 5% OF THE WEIGHT OF A FURNISHING MUST CONTAIN LESS THAN 100 PPM OF AT LEAST 4 OF THE 5 CHEMICAL GROUPS.</b>	
	He : Up to 2 pts	<p><b>Chemically inert material</b>                      Direct influence: PANOPREY®:                      - 0% heavy metals including mercury, cadmium, lead and antimony;                      - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS);                      - 0% pentachlorophenol                      - 0% protective products (e.g. lacquer, varnish etc.)                      As for all its products, PANOPREY® contains no chemical substances included in the candidate list of Substances of Very High Concern - SVHC - in concentrations higher than 0.1% of the mass.</p> <ul style="list-style-type: none"> <li>• ATT - Certificate of compliance REACH - FR - EN</li> <li>• ATT - Certificate of compliance RoHS - FR - EN</li> <li>• ATT - Certificate of compliance - Panoprey - Fire retardant Fiber board - FR - EN</li> <li>• ATT - Certificate of compliance - Panoprey - Fire retardant faced board - FR - EN</li> </ul>
<b>Furniture and medical furnishings</b> Option 3 - Multi-Attribute Assessment of Products	<b>USE PRODUCTS THAT MEET ONE OF THE FOLLOWING CRITERIA:                      - COMPLIANT ENVIRONMENTAL DECLARATION                      - RESPONSIBLE SUPPLY</b>	
	He : Up to 2 pts	<p><b>Product made from PEFC™ or FSC® certified wood and with a conform life cycle analysis</b>                      Direct influence: Polyrey has carried out Life Cycle Analysis (LCA) for PANOPREY® in compliance with the NF EN 15804:2012+A1:2014 standard on collective environmental declarations.                      All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request*, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests.                      *Depending on the certification of our suppliers, while stocks last</p> <ul style="list-style-type: none"> <li>• ATT - FDES - Panoprey - Qualite Standard - FR</li> <li>• ATT - FDES - Panoprey - Qualite Hydrofuge - FR</li> <li>• ATT - EDPD - Panoprey - Standard quality - EN</li> <li>• ATT - EDPD - Panoprey - Moisture resistant quality - EN</li> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> </ul>



# EQ - INDOOR ENVIRONMENTAL QUALITY

Criterion	Requirement - Polyrey product contribution - Documentation													
<b>Low-emitting materials</b> Option 1 - Product category calculations or Option 2 - Budget calculation method	<b>RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.</b>													
	Up to 3 pts	<b>Product respecting TVOC and formaldehyde emissions thresholds.</b> In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. PANOPREY® has received the following classification:												
		<table border="1"> <thead> <tr> <th></th> <th>COVT</th> <th colspan="2">FORMALDEHYDE</th> </tr> <tr> <th></th> <th colspan="3">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> </thead> <tbody> <tr> <td>PANOPREY® CHIPBOARD - STANDARD QUALITY</td> <td>&lt; 1000 190 µg/m³</td> <td>A +</td> <td>&lt; 10 8,6 µg/m³</td> </tr> </tbody> </table>		COVT	FORMALDEHYDE			MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS			PANOPREY® CHIPBOARD - STANDARD QUALITY	< 1000 190 µg/m³	A +	< 10 8,6 µg/m³
	COVT	FORMALDEHYDE												
	MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS													
PANOPREY® CHIPBOARD - STANDARD QUALITY	< 1000 190 µg/m³	A +	< 10 8,6 µg/m³											
<ul style="list-style-type: none"> <li>• <a href="#">PV - Report of classification COV - Panoprey - Chipboard - Standard quality - FR-EN</a></li> </ul>														
<b>Interior lighting</b> Option 2 - Lighting quality	<b>CHOOSE 4 OF THE 8 SOLUTIONS AVAILABLE WHICH GUARANTEE QUALITY LIGHTING.</b>													
	0 : 1 pt Ho : 1 pt	<b>Product easing natural lighting</b> Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 180 decors (plain, wood, materials), PANOPREY® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.												
<ul style="list-style-type: none"> <li>• <a href="#">DOC - Light Reflectance Values</a></li> </ul>														

MY EXPERT



Environmental advice

Do not hesitate to contact us. Our team is at your disposal to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

DOWNLOAD ALL DOCUMENTARY PROOFS HERE :



## MELAMINE FACED-BOARD PANOPREY®

Interior Fitting



- NEW CONSTRUCTION
- REFURBISHMENT

LEED v4 - Interior Design and Construction (ID+C)  
Office (O) - Retail (R) - Hospitality (Ho)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design...) and to the materials, products and equipment within it. Depending on the certification, the table here below shows how the Polyrey product fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and details how the Polyrey product is concerned and answers them. At the end of the document you will find a clickable link allowing access to the documentary proofs.

Credit category		Credit	Requirement - Polyrey product contribution	Points
 MR MATERIALS AND RESOURCES		<b>Building Product Disclosure and Optimization - Environmental Product Declarations</b>	Option 1 - Environmental Product Declaration (EPD) - Product with conform life cycle analysis	1 pt
		<b>Building Product Disclosure and Optimization - Sourcing of Raw Materials</b>	Option 2 - Leadership extraction practice - Product made from PEFC™ ou FSC® certified wood	1 pt
		<b>Building Product Disclosure and Optimization - Material Ingredients</b>	Option 2 - Material Ingredient Optimization - Chemically inert material	1 pt
 EQ INDOOR ENVIRONMENTAL QUALITY		<b>Low-emitting materials</b>	Option 1 - Product category calculations or Option 2 - Budget calculation method - Product respecting TVOC and formaldehyde emissions thresholds	Up to 3 pts
		<b>Interior lighting</b>	Option 2 - Lighting quality - Product easing natural lighting	1 pt



# MR - MATERIALS AND RESOURCES

Criterion	Requirement - Polyrey product contribution - Documentation	
<b>Building Product Disclosure and Optimization</b> Environmental Product Declarations Option 1 - Environmental Product Declaration (EPD)	<p><b>USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.</b></p> <p><b>1 pt</b></p> <p><b>Product with conform life cycle analysis</b>                      Indirect influence: Polyrey has carried out Life Cycle Analysis (LCA) for PANOPREY® in compliance with the NF EN 15804:2012+A1:2014 standard on collective environmental declarations.</p> <ul style="list-style-type: none"> <li>• ATT - FDES - Panoprey - Qualite Standard - FR</li> <li>• ATT - FDES - Panoprey - Qualite Hydrofuge - FR</li> <li>• ATT - EPD - Panoprey - Standard quality - EN</li> <li>• ATT - EPD - Panoprey - Moisture resistant quality - EN</li> </ul>	
<b>Building Product Disclosure and Optimization</b> - <b>Sourcing of Raw Materials</b> Option 2 - Leadership extraction practice	<p><b>USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES (5 CRITERIA TO CHOOSE FROM).</b></p> <p><b>1 pt</b></p> <p><b>Product made from PEFC™ ou FSC® certified wood</b>                      PANOPREY® is:                      - 85% composed of an anhydrous wood core from the following sources: 20% roundwood (twigs, branches, downgraded logs), 37% related products (chips, particles) from other woodworking industries (sawmills, joineries, furniture makers, etc.), 43% secondary raw materials for recycling (chips from wood waste shredding).                      - All our products can be either PEFC™ (10-34-97) or FSC® CW (C068151) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (Depending on the certification of our suppliers, while stocks last)                      It is therefore included in the calculation of the volume of wood used in the structure, with reference to the order of 13 September 2010 establishing the method for calculating the volume of wood used in certain constructions.</p> <p>Moreover, Polyrey has one production plant in France : Ussel (19).</p> <ul style="list-style-type: none"> <li>• ATT - PEFC Certificate - EN</li> <li>• ATT - FSC Certificate - EN</li> <li>• ATT - European Timber regulations RBUE - FR - EN</li> </ul>	
<b>Building Product Disclosure and Optimization</b> - <b>Material Ingredients</b> Option 2 - Material Ingredient Optimization	<p><b>USE A CERTAIN NUMBER OF PRODUCTS WITH PRE-EVALUATED COMPONENTS.</b></p> <p><b>1 pt</b></p> <p><b>Chemically inert material</b>                      Direct influence: PANOPREY®:                      - 0% heavy metals including mercury, cadmium, lead and antimony;                      - 0% hexavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS);                      - 0% pentachlorophenol                      - 0% protective products (e.g. lacquer, varnish etc.)                      As for all its products, PANOPREY® contains no chemical substances included in the candidate list of Substances of Very High Concern – SVHC - in concentrations higher than 0.1% of the mass.</p> <ul style="list-style-type: none"> <li>• ATT - Certificate of compliance REACH - FR - EN</li> <li>• ATT - Certificate of compliance RoHS - FR - EN</li> <li>• ATT - Certificate of compliance - Panoprey - Fire retardant Fiber board - FR-EN</li> <li>• ATT - Certificate of compliance - Panoprey - Fire retardant Faced board - FR-EN</li> </ul>	



# EQ - INDOOR ENVIRONMENTAL QUALITY

Criterion	Requirement - Polyrey product contribution - Documentation													
<b>Low-emitting materials</b> Option 1 - Product category calculations or Option 2 - Budget calculation method	Up to 3 pts	<b>RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.</b>												
		<b>Product respecting TVOC and formaldehyde emissions thresholds.</b> In the framework of the French VOC label, Polyrey measures VOC emissions from its products in accordance with the ISO 16000 standard. PANOPREY® has received the following classification:												
		<table border="1"> <thead> <tr> <th></th> <th>COVT</th> <th colspan="2">FORMALDEHYDE</th> </tr> <tr> <th></th> <th colspan="3">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> </thead> <tbody> <tr> <td>PANOPREY® CHIPBOARD - STANDARD QUALITY</td> <td>&lt; 1000 190 µg/m³</td> <td>A +</td> <td>&lt; 10 8,6 µg/m³</td> </tr> </tbody> </table>				COVT	FORMALDEHYDE			MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS			PANOPREY® CHIPBOARD - STANDARD QUALITY	< 1000 190 µg/m³
	COVT	FORMALDEHYDE												
	MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS													
PANOPREY® CHIPBOARD - STANDARD QUALITY	< 1000 190 µg/m³	A +	< 10 8,6 µg/m³											
<ul style="list-style-type: none"> <li>• <a href="#">PV - Report of classification COV - Panoprey - Chipboard - Standard quality - FR-EN</a></li> </ul>														
<b>Interior lighting</b> Option 2 - Lighting quality	1 pt	<b>CHOSE 4 OF THE 8 SOLUTIONS AVAILABLE WHICH GUARANTEE QUALITY LIGHTING.</b>												
		<b>Product easing natural lighting</b> Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 180 decors (plain, wood, materials), PANOPREY® contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.04 for the N005 Black decor to 0.86 for the B117 Artic White decor.												
<ul style="list-style-type: none"> <li>• <a href="#">DOC - Light Reflectance Values</a></li> </ul>														

MY EXPERT



Environmental advice

Do not hesitate to contact us. Our team is at your disposal to advise and support you.

polyrey.export@polyrey.com - Tel : +33 (0)5 53 76 56 88

DOWNLOAD ALL DOCUMENTARY PROOFS HERE :

